F - TYPE Connectors





GENERAL INFORMATION

F type battery connoctors are flexible products that allow the traction battery cells to be connected to each other. F type battery connectors are assembled to the battery cells with a specially insulated bolt that does not require a cover.

FEATURES

High current carrying capacity

High flexibility

High impermeability (Special cable insulation and injection materials)

Standart products comply eith GWT 650 (IEC 60695-2-11)

There is also VO UL94 / GWT 750 version in order to use in the environments where heat resistance is expected to be high (Mining etc.)

Terminal pull-out force complies with MIL-T 7928

100% resistance control and marking

Insulation resistance 1000 (Under 500 VDC)

Protection rating is IP55 (IEC 60529-1)


Thin plated terminals

%99.9 Copper terminals




- TYPE Connectors


FLEXIBILTY TABLE



Mini	Minimum flexiblity length(L2) table according to the connector lenght(L1)				L1)		
Connector	Cable	L2					
Type:	Section:	L1 85mm	L1 95mm	L1 110mm	L1 130mm	L1 150mm	L1 150mm
	25mm²	60mm	40mm	30mm	30mm	30mm	30mm
	35mm²	60mm	40mm	30mm	30mm	30mm	30mm
F Type:	50mm²	70mm	65mm	35mm	30mm	30mm	30mm
(Flex)	70mm²			75mm	55mm	35mm	35mm
	95mm²			85mm	45mm	45mm	35mm

DIMENSIONS (mm)





Cable Section	Α	А	А
25mm ²	2	4.75	16.50
35mm ²	2	4.75	16.50
50mm²	2	5.60	17.50
70mm²	3	6.00	19.50
95mm²	3	6.20	23.50

F - TYPE Connectors

Product List



4	Product Code	Cable Section	L1(mm)
	MEKN71000011	25mm ²	75
	MEKN71000089	9 25mm²	80
	MEKN71000095	5 25mm ²	85
	MEKN71000010) 25mm²	90
	MEKN71000009	9 25mm²	95
	MEKN7100000	3 25mm ²	110
	MEKN71000119	25mm ²	150
	MEKN71000102	25mm ²	275
	MEKN71000096	5 25mm ²	300
	MEKN71000091	25mm ²	600

Product Code	Cable Section	L1(mm)
MEKN7100000	0 35mm²	75
MEKN7100000	7 35mm²	80
MEKN71000039	35mm ²	85
MEKN7100000	35mm ²	95
MEKN71000002	2 35mm ²	110
MEKN71000012	35mm ²	130
MEKN71000013	35mm ²	150
MEKN71000014	- 35mm²	170
MEKN71000121	35mm ²	190
MEKN71000103	35mm ²	285
MEKN71000093	35mm ²	300
MEKN71000100	35mm ²	380

Product Code	Cable Section	L1(mm)
MEKN71000031	95mm ²	80
MEKN71000032	2 95mm²	95
MEKN71000033	3 95mm²	110
MEKN71000034	4 95mm²	130
MEKN71000035	5 95mm²	150
MEKN71000036	5 95mm²	170
MEKN71000038	3 95mm²	210
MEKN71000098	3 95mm²	380
MEKN71000099	9 95mm²	1200

Product Code	Cable Section	n L1(mm)
MEKN71000016	50mm ²	80
MEKN7100009	4 50mm ²	90
MEKN7100000	3 50mm ²	95
MEKN7100000	4 50mm ²	110
MEKN71000017	′ 50mm²	130
MEKN71000018	3 50mm ²	150
MEKN71000019	50mm ²	170
MEKN7100002	0 50mm ²	210
MEKN71000104	50mm ²	275
MEKN71000105	50mm ²	285
MEKN7100008	5 50mm ²	300
MEKN7100008	1 50mm ²	310
MEKN7100009	7 50mm ²	350
MEKN71000101	50mm ²	500

Product Code	Cable Section	L1(mm)
MEKN71000092	2 70mm²	80
MEKN71000005	5 70mm ²	95
MEKN71000022	2 70mm ²	110
MEKN71000023	3 70mm ²	130
MEKN71000024	4 70mm²	150
MEKN71000025	5 70mm ²	170
MEKN71000026	5 70mm ²	190
MEKN71000027	7 70mm²	210
MEKN71000106	70mm ²	275
MEKN71000107	70mm ²	285
MEKN71000120	70mm ²	300
MEKN71000084	4 70mm ²	310

Please contact us for different length and cable section reguests.



UT.TS1 Rev:00 3